



# MATERIAL SAFETY DATA SHEET - SEALMASTER

## SECTION 1 - PRODUCT IDENTIFICATION AND USE

Product Name: Hydro-Seal Sealmaster  
Product ID No. Not Regulated WHMIS Class:  
  
Product Use: Hydrophilic Paste  
  
Manufacturer Euro Polymers Technologies Ltd.  
St.James Square, Bacup, Lancashire  
OL13 9AA, United Kingdom

## SECTION 2 - HAZARDOUS INGREDIENTS

Ingredient	%	CAS#
Tetramethylxylene diisocyanate aromatic Hydrocarbons	<2 <6	2778-42-9 64742-95-6

## SECTION 3 - PHYSICAL DATA

Physical State: Paste  
Odor & Appearance: Faint, Grey  
Odor Threshold: Not Available  
Vapor Pressure: N/A  
Vapor Density: N/A  
Evaporation Rate: Low  
Boiling Point: 0°C/3  
Freezing Point: N/A  
pH: N/A  
Specific Gravity: N/A

## SECTION 4 - FIRE AND EXPLOSION DATA

Flammability: No  
Means of extinction: Carbon Dioxide, Halon  
Flashpoint: N/A  
Upper Flammable Limit: N/A  
Lower Flammable Limit: N/A  
Autoignition Temperature: 200C  
Hazardous Combustible Products: CO - CO<sub>2</sub>  
Explosion Data: Not Applicable

## SECTION 5 - REACTIVITY DATA

Chemical Stability: Yes  
  
Reactivity: None  
Hazardous Decomposition Products: CO - CO<sub>2</sub>

## SECTION 6 - TOXICOLOGICAL PROPERTIES

Route of Entry:  
Skin Contact: Yes Skin Absorption: Yes  
Eye Contact: Yes Inhalation: Yes  
Ingestion: Yes  
Effects of Acute Exposure:  
Skin: Irritation  
Eyes: Irritation  
Inhalation Irritation  
Ingestion: Nausea, Vomiting  
Effects against Chronic Exposure to Products: Not available  
Exposure Limits: Not Available  
Irritancy of Product: Eye, and skin irritation  
Sensitization to Product: Skin  
Carcinogenicity: Not listed by the IARC  
Teratogenicity: Not Available Reproductive Toxicity: Not Available  
Mutagenicity: Not Available Synergistic Products: Not Available

## SECTION 7 - PREVENTIVE MEASURES

### Personal Protective Equipment:

Use safety goggles.  
Use PVC or neoprene industrial gloves.  
Use protective clothing, with long sleeves and long pants.  
Maintain eye bath in work area.

### Engineering Controls:

Use in mechanically ventilated areas.

### Leak and Spill Procedure:

Absorb with conventional absorbents  
Dispose according to local regulations.

### Waste Disposal:

Absorb with conventional absorbents  
Dispose according to local regulations.

### Handling Procedures and Equipment:

Handle with care.  
Do not open containers until at working place.

### Storage Requirements:

Keep containers dry and tightly closed. Store between 5 to 25 deg c  
Not permanently affected by freezing.  
Warm up materials prior to use.

### Special Shipping Instructions: None

## SECTION 8 - FIRST AID MEASURES

Skin Contact: Wash with lots of water  
  
Eye contact: Wash with lots of water  
and seek medical attention.  
  
Ingestion: Wash out mouth with water, seek medical attention

## SECTION 9 - PREPARATION DATE OF MSDS

Prepared by : Specton Construction Products Ltd.  
Phone: 1-866-773-2866  
Date January 4, 2018